

## DRI-PREP™

### Dry acid crystals



#### DESCRIPTION

DRI-PREP™ will clean and etch concrete surfaces. DRI-PREP™ is used instead of Muriatic Acid to both clean and etch concrete surfaces. It will neutralize the alkalinity of concrete, which has aged less than 6 months, and will also provide a slightly rougher surface for better adhesion prior to coating.

#### USES

- DRI-PREP™ can be used to remove dirt, grease, efflorescence, and dry mortar from masonry and unglazed ceramic tile surfaces.
- Neutralize alkalinity of concrete.

#### PRODUCT ADVANTAGES

- Safer than Muriatic acid.
- Safe to store.
- Safe to handle.
- Dissolves easily and quickly.

#### YIELD/COVERAGE

##### 2 lb Pail

- 400 square feet with cleaning mixture.
- 200 square feet with etching mixture.

##### 50 lb Pail

- 10,000 square feet with cleaning mixture.
- 5,000 square feet with etching mixture.

#### PACKAGING

- 2 lb pails
- 50 lb pails

### HOW TO USE

#### SURFACE PREPARATION

Remove all loose and powdered material from surface with a wire brush. Clean the surface of all dirt, grease and oil using TIGERCLEAN™ XT. Allow the surface to dry thoroughly.

**NOTICE:** Be sure to wear rubber gloves when handling DRI-PREP™.

#### TYPICAL TECHNICAL DATA FOR DRI-PREP™

Storage Conditions	Store in dry conditions at 40°F - 95°F.
Shelf Life	1 year
Color	White crystal, dissolves clear.

#### MIXING

##### 2 lb. Pails

**CLEANING:** Add contents to 4 gallons of warm water. Stir until completely dissolved. Use only a plastic container as DRI-PREP™ will etch galvanized surfaces.

**ETCHING:** Add contents to 2 gallons of warm water. Stir until completely dissolved. Use only a plastic container as DRI-PREP™ will etch galvanized surfaces.

##### 50 lb. Pails

**CLEANING:** Add contents to 100 gallons of warm water. Stir until completely dissolved. Use only a plastic container as DRI-PREP™ will etch galvanized surfaces.

**ETCHING:** Add contents to 50 gallons of warm water. Stir until completely dissolved. Use only a plastic container as DRI-PREP™ will etch galvanized surfaces.

#### APPLICATION & PLACEMENT

**CLEANING:** Apply to surface using a stiff, fiber brush and allow to remain on the surface at least 20 minutes or until all excess material has dissolved. Flush surface thoroughly with water and allow to dry completely before applying a coating.

**ETCHING:** Apply to surface using a stiff, fiber brush and allow to remain on the surface for at least 20 minutes. Flush surface thoroughly with water and allow to dry completely before applying a coating.

#### LIMITATIONS

The user is responsible for proper application. Garon personnel field visits are for the purpose of providing technical assistance only and are not for providing quality control or supervision on the jobsite.

Contains Sulfamic Acid, CAS # 5329-14-6. Causes eye burns. Irritates nose, throat and skin. Avoid contact with skin, eyes and clothing. In case of contact, flush immediately with water for at least 15 minutes. For eyes, get immediate medical attention. If taken internally give 1 – 2 glasses of milk or water and call physician immediately. Avoid breathing dust. Use with adequate ventilation. Wash thoroughly after handling. Keep out of reach of children.

### CAUTION

#### FIRST AID

Skin contact- wash thoroughly with soap & water. If any product gets into the eye, rinse immediately and repeatedly with water for at least 15 minutes. For respiratory problems, remove person to fresh air. Wash clothing before re-use.

#### CLEAN UP

Contain spills. Ventilate area. Use absorbent materials to collect. Dispose of according to local, state, federal regulations.

Mixed components—uncured material can be removed with an approved xylene or keytone solvent. Cured material must be removed by mechanical means.



Keep container tightly closed. Not for internal consumption--consult MSDS for additional information. This product is for professional use only.

**KEEP OUT OF REACH OF CHILDREN**

PRODUCT ITEM #13910 & 13920  
Garon and DRI-PREP are trademarks of Garon Products Inc.  
Made in USA.  
Printed January 2002.

**GARON PRODUCTS INC.**  
P.O. Box 1924  
Wall, NJ 07719-1924  
800-631-5380  
FAX 732-223-2002  
[www.garonproducts.com](http://www.garonproducts.com)

---

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and seller.

---

# TIGERCLEAN™ CTR



## Heavy-Duty Cleaner Degreaser with Citrus Fragrance



### DESCRIPTION

Tigerclean™ CTR is an exceptional blend of surfactants and emulsifiers plus natural citrus solvents.

Tigerclean™ CTR with its pleasant orange scent deodorizes and quickly and effectively penetrates the worst grease and oil residue left behind by petroleum-based grime to make cleaning fast and complete. Contains no Butyl Cellosolve. The addition of a natural solvent derived from the skin of citrus fruit makes this industrial grade cleaner even more effective on petroleum, animal and vegetable greases. May be used with a mop, bucket or spray application. Tigerclean™ CTR is safe for use with pressure washers and automatic scrubbers. It is just as aggressive in hot or cold, hard or soft water. Delivers all the benefits of Butyl without the hazards.

### USES

Floors, loading docks, stainless steel, cleaning of equipment, anywhere you need fast effective cleaning and degreasing. Not for use on glass or aluminum surfaces.

### PACKAGING

- 5-gallon pail

### APPLICATION & PLACEMENT

The amount of product needed for an individual cleaning job will depend on the amount and type of soil. These dilutions are therefore recommended start points and should be decreased or increased based on experience with your particular cleaning job.

### FOR USE IN AUTOMATIC SCRUBBERS:

Dilute 6-12 ounces per gallon of water. Hot water works best.

**PRESSURE WASHER:** Dilute product 6 ounces per one gallon of water.

**FOR STEAM CLEANING:** To the concentrate solution tank, mix 4 to 14 ounces to each gallon of water. Adjust the solution tank valve to obtain amount of cleaner required for different soil conditions.

**MOP & BUCKET:** 1 pint to 1 quart in three gallons of water (1:12 to 1:24).

### Typical Technical Data for Tigerclean™ CTR

Typical Technical Data for Tigerclean™ CTR	
Appearance	Clear liquid
Odor	Citrus
VOC Content	.75 grams / liter (Concentrate)
Specific Gravity	1.060±0.005
Density	8.85±0.05 lb./gallon
pH	13.0±0.5
Biodegradability	Complete
Viscosity	Water thin

**SPRAY CLEANING:** Dilute 6 ounces per gallon of water and apply with sprayers.

**FOR SOAK TANK OR ULTRASONICS:** This product can be used at 12 ounces per gallon of water. (1:10)

### SLIP & FALL HAZARDS

Ensure cured coating surface remains dry in pedestrian, equipment and vehicular areas to avoid slips and falls of people, equipment and vehicles. Use caution when coating is wet or when oil, hydraulic fluids, grease or other chemicals, fluids or agents that may produce a slick surface are present. Increase slip resistance by broadcasting an appropriate size aggregate into the wet coating during application in all areas where enhanced coating traction may be necessary. **Be aware of the full cure time. Do not open the area to normal service, harsh industrial chemical or abusive use before the coating is fully cured.**

### DISCLAIMER

The information and recommendations set forth in this document are based upon tests conducted by or on behalf of Garon Products, Inc. Such recommendations and information set forth herein are subject to change and pertain to the product(s) offered at the time of publication. Published technical data and instructions are subject to change without notice. Consult [www.garonproducts.com](http://www.garonproducts.com) or call 800-631-5380 to obtain the most recent Product Data, SDS and Application instructions. This is not a controlled document.

### COLOR

Applied samples, color charts, illustrations and reproductions in catalogs and other Garon publications are not guaranteed to match the color shades of materials ordered. Colors or clarity for clear may be affected by high humidity, low temperatures, or chemical exposure. Tire contact may cause discoloration. Slight lot-to-lot color variations may occur. Light or bright colors (white, safety yellow, etc.) may require multiple coats or a suitable color coordinated primer to achieve a satisfactory hide. When ordering to match a previous color, inquire if the same lot number or quality control number is still available. Colors may vary from batch to batch, therefore, use only product from the same batch for an entire job.

### FIRST AID

Skin contact- wash thoroughly with soap & water. If any product gets into the eye, rinse immediately and repeatedly with water for at least 15 minutes. For respiratory problems, remove person to fresh air. Wash clothing before re-use. Dust may cause skin or eye irritation. Wear gloves, eye and nuisance protection. **Consult SDS** and call for medical care if necessary.

### LIMITATIONS

The user is responsible for proper application.



**CAUTION**

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed.

**Keep container tightly closed. Not for internal consumption--consult MSDS for additional information. This product is for professional use only.**

**KEEP OUT OF REACH OF CHILDREN.**

Garon and **Tigerclean™ CTR** are trademarks of Garon Products Inc.  
Made in USA.

**GARON PRODUCTS INC.**  
P.O. Box 1924  
Wall, NJ 07719-1924  
800-631-5380  
FAX 732-223-2002  
[www.garonproducts.com](http://www.garonproducts.com)

---

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and seller.