

# GARON GRIT™ 30

## Anti-Skid, Abrasion-Resistant Grain



### DESCRIPTION

GARON-GRIT™ 30 is an anti-skid grain that is an extremely hard, abrasion resistant, chemically inert, fused quartz.

### USES

GARON GRIT™ 30 is used in preparation of non-slip surfaces.

### APPLICATION & PLACEMENT

After mixing the Garon floor coating of your choice pour in ribbons on floor. Broadcast Garon Grit™ 30 at 1 lb. per square foot into wet coating, then complete the job by roller applying a Garon thick build topcoat.

Garon Grit™ 30 is also sprinkled into wet coatings at one lb. per 100 square feet (or more if more traction is desired) to create enhanced coating traction.

### LIMITATIONS

The user is responsible for proper application.

**Keep container tightly closed. Not for internal consumption--consult MSDS for additional information. This product is for professional use only.**

**KEEP OUT OF REACH OF CHILDREN**

TYPICAL DATA FOR GARON GRIT™ 30	
Storage	Store at room temperature
Boiling Point	4,046°F
Specific Gravity	2.65
Melting Point	3,050°F
Particle Shape	Irregular, sharp edged

PRODUCT ITEM 32100  
Garon and GARON GRIT 30 are  
trademarks of Garon Products Inc.  
Made in USA.  
Printed January 2002.

**GARON PRODUCTS INC.**  
P.O. Box 1924  
Wall, NJ 07719-1924  
800-631-5380  
FAX 732-223-2002  
[www.garonproducts.com](http://www.garonproducts.com)