

GRIP-COAT™ PRIMER

Acrylic Primer



DESCRIPTION

Clear, acrylic primer for concrete pavement surfaces designed to promote adhesion of Grip Coat™ Recreational Surface

Resurfacer. **Grip-Coat™ Primer** is a clear drying, one part water-based acrylic emulsion.

YIELD/COVERAGE

Approximately 300-400 square feet per gallon depending on surface porosity.

MIXING

Stir thoroughly before using. Apply **Grip-Coat™ Primer** as is. **Do Not Dilute.**

IMPORTANT: Stir before using. Temperatures must be above 50°F both during application and for a period of at least 24 hours after application. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

APPLICATION & PLACEMENT

Use roller or broom to apply. Apply a thin coat of **Grip-Coat™ Primer** at the rate of 300-400 square feet per gallon. Do not leave excess build-up of material on surface. Allow **Grip-Coat™ Primer** to dry completely before applying **Grip-Coat™**.

All dirt, oil, dust, foreign contaminants, peeling coating and laitance must be removed from surface prior to coating to assure a trouble free bond. Previously coated floors exhibiting a strong bond to surface can be coated over by sanding down the existing coating.

Refer to Garon's Master Surface Preparation & Moisture Guideline for complete details.

MIXING AREA

Select a suitable mix area and protect the floor surface from accidental resin spillage with a layer of cardboard and/or plastic sheet. Provide enough space for free unimpeded movement for mixing activity. The more comfortable your surroundings in the mix area, the less likely your mixers are to have an error. Have all necessary tools ready: slow speed drills, mix and measure containers, etc. **Do Not Start Mixing**

Technical Data for Grip-Coat™ Primer

Technical Data for Grip-Coat™ Primer	
Storage Life	One year
Set Time	45-90 minutes under optimum conditions
Classification	Acrylic emulsion
Flammability	Non flammable
Weight per Gallon at 77°F	8.7 pounds
Flash Point	None
Color	Milky white. Clear when dry.

Materials Until Ready for Immediate Use.

Once material is finished being mixed, it must be used immediately. Prior to mixing apply masking tape wherever coating is intended to stop. Keyed edges must be installed at edge termination points to protect the material from chipping damage and to obtain a clean, straight edge.

Allow concrete to dry completely before applying **Grip-Coat™ Primer**.

Asphalt: Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials. Repair of pavement surface defects, depressions and cracks should be complete prior to application.

SLIP & FALL HAZARDS

Ensure cured coating surface remains dry in pedestrian, equipment and vehicular areas to avoid slips and falls of people, equipment and vehicles. Use caution when coating is wet or when oil, hydraulic fluids, grease or other chemicals, fluids or agents that may produce a slick surface are present. Increase slip resistance by broadcasting an appropriate size aggregate into the wet coating during application in all areas where enhanced coating traction may be necessary. **Be aware of the full cure time.**

Do not open the area to normal service, harsh industrial chemical or abusive use before the coating is fully cured.

CLEAN UP

Contain spills. Ventilate area. Use absorbent materials to collect. Dispose of according to local, state, federal regulations. Mixed components — uncured material can be removed with an approved xylene or ketone solvent. Cured material must be removed by mechanical means.

FIRST AID

If ingested **do not** induce vomiting and get prompt medical attention. Skin contact—wash thoroughly with soap & water. If any product gets into the eye, rinse immediately and repeatedly with water for at least 15 minutes. For respiratory problems, remove person to fresh air. Wash clothing before re-use. Dust may cause skin or eye irritation. Wear gloves, eye and nuisance protection. **Consult SDS.**

LIMITATIONS

The user is responsible for proper application.

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed.

Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. When not in use, keep containers tightly closed and upright to prevent leakage.



Keep container tightly closed. Not for internal consumption--consult MSDS for additional information. This product is for professional use only.

KEEP OUT OF REACH OF CHILDREN

NOTICE TO BUYER:

DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may **CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.**